



Eclat **E** Series

- ◆ Cooler Running
- ◆ Easy Rolling
- ◆ Environmental Friendly



Armadillo Tire LLC

WWW.ARMADILLOTIRE.COM Toll free : (855)860-5618
317 South McLennan Loop Elm Mott, TX 76640

Eclat



Eclat is the ultimate problem solver. Eclat utilizes the highest grades of natural rubber in a 4-stage construction. Because Eclat has braided wire in the bead area; it will not spin on the wheel. Eclat should be considered where other tires fall short and where the cost conscience buyer seeks the lowest overall cost per hour.

Size & Specifications

TYRE SIZE	STANDARD RIM	Heel Tyre		Dimensions (inch)		Load Capacity(lbs)					
		Quick	Standard	Section Width	Overall Diameter +/-2%	Forklift		Other Vehicles			Static (0 km/h)
						Load Wheel 25km/h	Steer Wheel 25km/h	6km/h	10km/h	25km/h	
15x4 1/2-8(125/75-8)	3.00D-8	◆	◆	4.6	15.0	2293	1764	2293	2072	1764	2668
5.00-8	3.00D-8	◆	◆	5.1	18.1	3122	2405	3122	2835	2405	3630
	3.50D-8	□	□	5.4							
16x6-8(150/75-8)	4.33R-8	◆	◆	6.1	16.4	3299	2538	3299	2990	2538	3828
18x7-8(180/70-8)△	4.33R-8	◆	◆	6.2	18.1	4733	3641	4733	4292	3641	5494
6.00-9	4.00E-9	◆	◆	6.1	20.8	4159	3199	4159	3773	3199	4832
21x8-9(200/75-9)	6.00E-9	◆	◆	7.5	20.9	6079	4678	6079	5527	4678	7061
6.50-10	5.00F-10	◆	◆	6.5	22.8	5163	3972	5163	4689	3972	6002
200/50-10	6.50F-10	◆	◆	7.8	18.2	5450	4192	5450	4943	4192	6333
23x9-10(225/75-10)	6.50F-10	◆	◆	8.0	23.3	7602	5847	7602	6895	5847	8826
7.00-12	5.00S-12	◆	◆	6.9	25.9	6443	4943	6443	5836	4943	7458
23x10-12(250/60-12)	8.00G-12	◆	◆	9.2	23.1	8319	6399	8319	7546	6399	9665
27x10-12(250/75-12)	8.00G-12	◆	◆	9.8	27.2	8605	6620	8605	7811	6620	9996
6.00-15	4.50E-15	□	□	6.3	27.5	6013	4623	6013	5450	4623	6984
8.25-15	6.50-15	◆	◆	8.5	32.6	10150	7811	10150	9212	7811	11794
28x9-15(8.15-15)225/75-15	7.00-15	◆	◆	8.8	27.4	8319	6399	8319	7546	6399	9665
250-15(200/75-15)	7.00-15	◆	◆	9.0	28.7	10470	8054	10470	9267	8054	12158
	7.50-15	◆	◆	9.1							
28x12.5-15(335/45-15)	9.75-15	◆	◆	11.8	28.3	12191	9378	12191	11066	9378	14166
300-15(315/70-15)	8.00-15	◆	◆	10.2	32.7	12908	9929	12908	11717	9929	14993
355/65-15(32x12.1-15)	9.75-15	□	□	11.9	31.9	17211	13239	15446	14188	12026	19991
10.00-20	7.50-20	□	□	10.0	41.7	13239	11033	13239	12026	11033	16659
	8.00-20	◆	◆	10.1							
11.00-20	7.50-20	□	□	10.0	42.3	14431	12026	14431	13107	12026	18160
	8.00-20	◆	◆	10.1							
12.00-20	8.00-20	◆	◆	11.3	43.5	16681	13901	16681	15148	13901	20995
	8.50-20	◆	◆	11.4							

△ The rim contour may vary from different vehicle manufacturers, please contact with EXMILE technical department for details.

◆ Available

□ Under Development